





















Product quality						
Formats		Basic 200 (Utility class 23 + 31)	Basic 200 V (Utility class 23 + 31)	Basic 400 / 400 V (Utility class 23 + 32)	Basic 600 V (Utility class 23 + 32)	
		1285 x 194 x 7 mm	1285 x 194 x 7 mm	1285 x 194 x 8 mm	1285 x 243 x 8 mm	2200 x 243 x 8 mm
Packaging	Pack:	12 Elements	11 Elements	10 Elements	7 Elements	6 Elements
		2.991 m ² / 19.64 kg	2.742 m ² / 18.9 kg	2.493 m ² / 17.6 kg	2.186 m ² / 15.46 kg	3.208 m ² / 22,73 kg
	Pallet:	40 Pack	40 Pack	40 Pack	42 Pack	39 Pack
		119.66 m ² / 800 kg	109.69 m ² / 771 kg	99.716 m ² / 719 kg	91.80 m ² / 665 kg	125.1 m ² / 902.4 kg
Guarantee		12 Years (According Parador guarantee conditions)			Notes	- not ready for glue-down
Domestic area:						- cleaning an maintenance see instructions
Commercial area:						- technical changes reserved

Product labelling					Tolerances (EN 13329)		
 EN 14041 : 08				 Quality Functionality Production Controlled www.tuv.com ID 11112-12656-001		Squareness of elements (≤ 0,20 mm)	≤ 0.10 mm
					Determining the straightness of the edges (≤ 0,30 mm/m)	≤ 0.10 mm/m	
					Height differences of the elements	(average ≤ 0.10 mm)	aver. ≤ 0.05 mm
						(max. ≤ 0.15 mm)	max. ≤ 0.10 mm
					Opening between installed elements	(average ≤ 0.15 mm)	aver. ≤ 0.05 mm
						(max. ≤ 0.20 mm)	max. ≤ 0.10 mm
					Block alignment	± 2 mm	

Classification product features							
		Test standard	Rating			Test standard	Rating
	Utility class 23 domestic areas with intensive use	EN 13329	Living room, hall, kitchen, home office		Slip resistance	EN 13893 EN 14041	μ ≥ 0.35 DS
	Utility class 31 commercial areas with medium use	EN 13329	Hotels, small offices		Electrical behaviour	EN 1815	-
	Utility class 32 commercial areas with medium use	EN 13329	Classrooms, small offices, shops		Thermal resistance Suitable for installation over underfloor heating when using an appropriate underlay and moisture barrier.	EN 12664	0.043 m ² *K/W
	Abrasion	EN 13329, Annex E	Basic 200: AC 3 (≥ 2.000 rev.) Basic 400/600: AC 4 (≥ 4.000 rev.)		Resistance to roller castor chairs	EN 425	No visible changes
	Impact resistance	EN 13329, Annex F	Basic 200: IC 1 Basic 400-600: IC 2		Effect of a furniture leg	EN 424	No visible changes
	Reaction to fire	EN 13501-1	C _{fl} s1		Indentation-residual	EN 433	No visible changes
	Staining resistance	EN 438-2	Category 1 + 2: level 5 Category 3: level 4/5		Locking strength of mechanically assembled panels	ISO 24334	-
	Cigarette resistance	EN 438-2	level 4		Acoustical - Impact noise reduction	ISO 717-2	14 dB (with Akustik-Protect 100)
	Light fastness	EN ISO 105 - B02 EN 20105 - A02	Blue wool scale: Stage ≥ 6 Grey scale: Stage ≥ 4		Dimensional stability	ISO 24339	-
	Formaldehyde (E1 = 0.1 ppm)	EN 717-1	≤ 0.05 ppm		Surface soundness	EN 433	Basic 200/400: ≥ 1,6 N/mm ² Basic 200 V/400 V/600 V: ≥ 1,8 N/mm ²
	Thickness swelling	EN 13329, Annex G (≤ 18 %)	Basic 200/400: ≤ 15 % Basic 200 V/400 V/600 V: ≤ 13 %		Slip resistance on an inclined plane	DIN 51130	Depending on structure: -/R 9/R 10
	Scratch resistance	EN 438	Level 4		Disposal	Private waste disposal with normal household waste / bulky waste possible (EAK-Code-number 20 01 38).	

Changed:	QMB	File:	20170116_PA_TDS_Laminat_Basic_EN
Date:	01.01.2014	Updates at:	www.parador.eu/service/catalogues-downloads/technical-data-sheets
Our technical data sheets are constantly updated and adapted to the latest technology. This version replaces all earlier versions and is valid from:		16.01.2017	